

## **CP-9020-320**

### **PRODUCT DESCRIPTION**

CP-9020 series products are fully formulated gear and bearing lubricants based on semi-synthetic hydrocarbons basefluid. The CP-9020 series gear and bearing lubricants have excellent thermal and oxidative stability, combined with superior gear load carrying ability.

The semi-synthetic hydrocarbon base fluid has proved in extensive field evaluations to give extended life and overall economic benefits. These lubricants have high viscosity indexes, high film strength, and excellent mechanical shear resistance even in heavily loaded gear applications. Additives provide superior oxidative stability, corrosion protection and load carrying ability. Field test reports state that lower operating temperatures are possible due to reduction in heat build-up due to friction. The reduced friction may also reduce horsepower requirements up to five percent depending on other operating and environmental conditions.

<b>TYPICAL PROPERTIES*</b>	<b>CP-9020-320</b>
Viscosity@40°C,cSt, ASTM D445	308.98
Viscosity @100°C,cSt	30.33
Viscosity @100°F	348.70
Viscosity @210°F	31.28
Viscosity Index ASTM D2270	135
Density lb/gal, 60°F	7.21
Pour point °F (°C) ASTM D97	5(-15)
Flash point C.O.C.,°F (°C) ASTM D92	460(237)
Fire point C.O.C.,°F (°C) ASTM D92	465(240)
Specific Gravity, ASTM D1298	0.861

\* These values are not intended for use in preparing specifications

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: [www.pingyiao.com](http://www.pingyiao.com)

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)