

PARA-4

PRODUCT DESCRIPTION

PARA-4 is a custom-blended polyalphaolefin (PAO) partial synthetic hydrocarbon oil giving improved lubrication at high and low temperatures, reduced volatility, good chemical inertness and hydrolytic stability, and compatibility with mineral oils and equipment designed for use with mineral oils.

PARA-4 is a long life lubricant formulated especially for flooded screw compressor.

PARP-4 is non-toxic and carries no hazardous labels or warnings under the OSHA Right to Know Law 29 CFT 1910.1200.

| TYPICAL PROPERTIES** | PARA-4 |
|--|---------------|
| Viscosity @ 40°C, cSt, (SSU) ASTM D445 | 40(187) |
| Viscosity @ 100°C | 6.5(47.5) |
| Viscosity @ 100°F, | 45(210) |
| Viscosity @ 210°F, | 6.6(47.8) |
| Viscosity Index ASTM D2270 | 108 |
| Density, lb/gal, 60°F | 7.12 |
| Pour Point °F | <-35 |
| Flash Point, C.O.C °F (°C) ASTM D92 | 450(232) |
| Fire Point, C.O.C °F (°C) ASTM D92 | 495(257) |
| Acid Number | 0.018(Nil) |

**These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com