

CPI COMP OIL 68

PRODUCT DESCRIPTION

CPI Comp Oil series products are custom-formulated lubricants specifically designed for long life under the severe, demanding conditions normally encountered in recirculating systems such as rotary screw compressors.

CPI Comp Oil series products are based on highly refined "semi-synthetic", hydro-treated dewaxed paraffinic oil. This special refining coupled with state-of-the-art additive technology results in performance improvements beyond conventional mineral oils and many synthetic oils. Among these are:

Trading

- Exceptional oxidative stability
- Long life
- Rust and corrosion inhibited
- Improved economy
- Thermal and hydrolytic stability
- Consistent quality
- Lower equipment maintenance
- Viscosity stability
- Less frictional drag less downtime
- Improved performance
- Resistance to carbon build-up & low sludging tendency
- Low evaporation loss

Ş	TYPICAL PROPERTIES*	Comp Oil 68
	Viscosity@40°C,cSt,ASTM D445	68
	Viscosity@100°C,cSt	8.9
	Viscosity@100°F,cSt	76

Shanghai PingYiao Trading CO., Ltd.Tel: 86-21-64705533Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250Telephone helpline: 15900706965Fax: 86-21-64705533-209Website: www.pingyiao.comE-mail: info@pingyiao.com

Specializing in Synthetic Lubricants	Shanghai Pir	ıgYiao Tradiı	ng CO., Ltd.
Viscosity@	210°F,cSt		9.1
Viscosity Index	ASTM D2270		104
Density, lbs	s/gal, 60°F		7.22
Pour Point °F (°	C)ASTM D97		-38(-39)
Flash Point,C.O.C.,	°F(℃)ASTM D92		440(227)
Fire Point ,C.O.C.,	°F(°C)ASTM D92		470(243)
Specific Gravity	, ASTM D1298	C	.0.868
Water C	Content	0	40ppm
Demulsibility, ml oil/r	nl water/ml emulsi		40-40-0(2)
(separation	time, min.)	XY .	10 10 0(2)

*These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.Tel: 86-21-64705533Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250Telephone helpline: 15900706965Fax: 86-21-64705533-209Website: www.pingyiao.comE-mail: info@pingyiao.com