

## **CP-1542-32**

### **PRODUCT DESCRIPTION**

CP-1542-32 is custom-blended polyalkylene glycol (PAG)/ ester rotary screw air compressor lubricants. This formulation offers improved lubrication at high and low temperature, reduced volatility, and high viscosity index, plus excellent corrosion protection.

CP-1542-32 (typical properties shown below) is long life lubricants formulated with rust and oxidation inhibitors. Other viscosities are available for specific applications.

CP-1542-32 will not leave behind carbon residue/ varnish when it oxidizes as compared to hydrocarbon based products.

<b>TYPICAL PROPERTIES*</b>	<b>CP-1542-32</b>
Viscosity@40°C,cSt, ASTM D445	39.34
Viscosity@100°C,cSt	7.89
Viscosity@100°F,SUS	199.3
Viscosity@210°F, SUS	52.6
Viscosity Index ASTM D2270	177
Density, g/ml, 20°F	0.974
Flash Point, C.O.C., °F ASTM D92	510°F
Fire Point, C.O.C., °F ASTM D92	575°F
Color	Green
Pour Point	-51°C
Copper Corrosion	1a

\*These values are not intended for use in preparing specifications

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: [www.pingyiao.com](http://www.pingyiao.com)

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)