

**CP-4100-150****PRODUCT DESCRIPTION**

CP-4100-150 synthetic reciprocating compressor lubricants are excellent crankcase and cylinder lubricants for reciprocating compressors. They possess outstanding oxidation resistance and fire resistance with an extremely high autoignition temperature (880°F). These properties, combined with a low volatility and very low carbon and varnish deposit formation rate, contribute substantially to minimizing the explosion and fire hazards in air compressors. CP-4100-150 products have excellent demulsibility characteristics (water separation) and decrease valve leakage. The amount of oil in downstream air systems is greatly reduced when using CP-4100-150 product due to their low volatility and reduced lubricant requirements. Maximum compressor life with decreased maintenance is realized because of these properties and excellent film strength, wetting ability, lubricity, and corrosion protection.

<b>TYPICAL PROPERTIES**</b>	<b>CP-4100-150</b>
Viscosity @ 40°C, cSt, ASTM D445	154.25
Viscosity @ 100°C, cSt	12.69
Viscosity @ 100°F,	177.2
Viscosity @ 210°F,	13.1
Viscosity Index ASTM D2270	65
Density, lb/gal, 60°F	8.13
Pour Point °F (°C) ASTM D97	-25(-31)
Flash Point, C.O.C., °F (°C) ASTM D92	540(282)
Fire Point, C.O.C., °F (°C) ASTM D92	600(316)
Specific Gravity, ASTM D1298	0.997

\*These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: [www.pingyiao.com](http://www.pingyiao.com)

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)