

CP-4100-32

PRODUCT DESCRIPTION

CP-4100-32 product is high quality synthetic fluids based on premium dibasic acidester base stocks and formulated to provide superior oxidative and thermal stability.

Typical applications include rotary screw compressor lubricant/coolant, heat transfer fluid and other recirculating systems where long life and reduced fluid consumption are objectives. Lower maintenance costs are also a result of reduced varnish, sludge and carbon deposits. Additives have also been included to provide excellent lubricity and protection against rust and copper corrosion.

CP-4100-32 is readily biodegradable. Small amounts of this oil spilled or leaked onto the ground will not adversely affect the environment.

Disposal of these fluids should be done in accordance with Local, State, and Federal regulations.

TYPICAL PROPERTIES**	CP-4100-32
Viscosity @ 40°C ,cSt, ASTM D445	28.0
Viscosity @ 100°C, cSt	5.34
Viscosity @ 100°F ,	30.5
Viscosity @ 210°F ,	5.5
Viscosity Index ASTM D2270	130
Density, 1b/gal, 60°F	7.66
Pour Point °F (°C) ASTM D97	-60(-51)
Flash Point, C.O.C °F (°C) ASTM D92	480(249)
Fire Point, C.O.C °F (°C) ASTM D92	530(277)
Specific Gravity, ASTM D1298	0.918

** These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com