

CP-4601-15

PRODUCT DESCRIPTION

CP-4601 Series are custom-blended polyalphaolefin (PAO) synthetic hydrocarbon fluids giving improved lubrication at high and low temperatures, reduced volatility, and compatibility with mineral oils and equipment designed for use with mineral oils.

CP-4601 Series (typical properties shown below) are long life lubricants formulated with rust and oxidation inhibitors. Other viscosities are available for specific applications.

CP-4601 Series are authorized by USDA for use in federally inspected meat and poultry plants with no possibility of food contact (H-2)

TYPICAL PROPERTIES*	CP-4601-15
Viscosity@40°C,cSt,ASTM D445	17
Viscosity @100°C,cSt	3.8
Viscosity @100°F	18.2
Viscosity @210°F	3.9
Viscosity Index ASTM D2270	123
Density 1b/gal, 60°F	6.82
Pour point°F (°C) ASTM D97	-100(-73)
Flash point C.O.C.,°F (°C) ASTM D92	425(210)
Fire point C.O.C.,°F (°C) ASTM D92	480(249)
Specific Gravity, ASTM D1298	0.82

* These values are not intended for use in preparing specifications

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com