

CP-9003-32

PRODUCT DESCRIPTION

CP-9003 series products are custom formulated lubricants specifically designed for long life under the severe, demanding conditions normally encountered in recirculating systems such as rotary screw compressors. They have a very low vapor pressure, making it an excellent lubricant for vacuum applications.

CP-9003 series products are based on highly refined, hydrocracked dewaxed paraffinic oil. This special refining coupled with state of the art additive technology results in performance improvements beyond other compressor oils. Among these are:

Exceptional oxidative stability	Long life	
Less frictional drag	Less down time	
Low evaporation loss	Improved performance	
Viscosity stability	Consistent quality	
Thermal & hydrolytic stability	Lower equipment maintenance	
Rust and corrosion inhibited	Improved economy	
Resistance to carbon buildup and low sludging tendency		
THE		
TVDICAL DDODEDTIES**	CD 0003 3	

TYPICAL PROPERTI	ES**	CP-9003-32
Viscosity @ 40°C,cSt, A	STM D445	30.49
Viscosity @ 100°C, cSt		5.28
Viscosity @ 100°F		33.52
Viscosity @210°F		5.4
Viscosity Index ASTM I	02270	105
Density, 1b/gal, 60°F		7.2
Pour Point °F(°C) ASTM	1 D97	0(-18)
Flash Point, C.O.C °F (°C	C) ASTM D92	420(216)
Fire Point, C.O.C °F (°C) ASTM D92	450(232)

Shanghai PingYiao Trading CO., Ltd.Tel: 86-21-64705533Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250Telephone helpline: 15900706965Fax: 86-21-64705533-209Website: www.pingyiao.comE-mail: info@pingyiao.com



Specific Gravity, ASTM D1298

0.870

** These values are not intended for use in preparing specifications.

Shanahai Pines iao Tradines CO. Lich.

Shanghai PingYiao Trading CO., Ltd.Tel: 86-21-64705533Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250Telephone helpline: 15900706965Fax: 86-21-64705533-209Website: www.pingyiao.comE-mail: info@pingyiao.com