

CP-9126-100

CP-9126-100 is a custom-blended severely hydrocracked isodewaxed partial synthetic lubricant. Primary benefits include:

Extended 6,000-7,000 typical life

Very low deposit formation for extended valve life

Non-toxic and non-hazardous

Excellent wear protection

This high-performance lubricant is recommended for use in:

Reciprocating air compressors

TYPICAL PROPERTIES**

CP-9126-100

Viscosity @ 40°C, cSt, ASTM D445	93.6
Viscosity @ 100°C, cSt	10.8
Viscosity @ 100°F, SUS	491
Viscosity @ 210°F, SUS	63
Viscosity Index ASTM D2270	98
Density, lb/gal, 60°F, ASTM D4052	7.33
Pour Point °F (°C) ASTM D97	-15(5)
Flash Point, C.O.C., °F (°C) ASTM D92	520(271)
Fire Point, C.O.C., °F (°C) ASTM D92	570(299)
Specific Gravity, ASTM D4052	0.878

*These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com