

## Shanghai PingYiao Trading CO., Ltd.

# **ArChine Propana RGI 150**

### **Lubricant for Propane Refrigeration Compressor**

#### **Description**

ArChine Propana RGI 150 is blend of polyalkylene glycols with unique additives that is specifically designed for use in natural refrigerants such as propane and butane. The ability of ArChine Propana RGI 150 lubricant to withstand dilution by hydrocarbon and other compressed gas is particularly advantageous in flooded screw compressors.

ArChine Propana RGI 150 is an ideal fluid for these natural refrigerants such as propane and butane due to its very low pour point, high viscosity index, excellent solubility and superior resistance against viscosity dilution.

#### Attributes

- Specifically designed for use in refrigeration systems requiring PAG lubricants
- Excellent film strength and anti-wear properties for better protection of compressor parts
- Resists viscosity dilution
- Reduced hygroscopic tendencies
- Very high viscosity index for better lubrication and seal protection at extreme temperatures
- Excellent thermal and oxidative stability leading to longer fluid life and extended oil drain intervals
- Increased protection against rust, corrosion, carbon and varnish
- Very high flash points and auto-ignition points for added safety
- Non-toxic/non-hazardous

#### Applications

- Propane refrigeration compressor lubrication.
- Natural gas and other light hydrocarbon compressor applications.

#### **Typical Properties\***

Item	ArChine Propana RGI 150
Appearance	Colorless clear liquid
Density@20°C, g/cm <sup>3</sup>	0.992
Viscosity @ 40°C, mm²/s	151.0

#### **Distributor Wanted**

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533 Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai

200235 P.R.China

Telephone helpline: (86)15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com



# Shanghai PingYiao Trading CO., Ltd.

	0 0	
Viscosity @100°C, mm <sup>2</sup> /s	25.51	
Viscosity Index	203	
Flash Point(COC), °C	233	
Fire point, °C	251	
Pour Point, °C	-39	
Copper Corrosion, 100℃,3hr	1 grade	
Foam Characteristic, 24°C	10/0	
* The above data is typical data, not as	s product specifications.	

#### **Distributor Wanted**

Tel: 86-21-64705533 Shanghai PingYiao Trading CO., Ltd. Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai

200235 P.R.China

Telephone helpline: (86)15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com