

ArChine Propana RGI 68

Lubricant for Propane Refrigeration Compressor

Description

ArChine Propana RGI 68 is blend of polyalkylene glycols with unique additives that is specifically designed for use in natural refrigerants such as propane and butane. The ability of ArChine Propana RGI 68 lubricant to withstand dilution by hydrocarbon and other compressed gas is particularly advantageous in flooded screw compressors.

ArChine Propana RGI 68 is an ideal fluid for these natural refrigerants such as propane and butane due to its very low pour point, high viscosity index, excellent solubility and superior resistance against viscosity dilution.

Attributes

- Specifically designed for use in refrigeration systems requiring PAG lubricants
- Excellent film strength and anti-wear properties for better protection of compressor parts
- Resists viscosity dilution
- Reduced hygroscopic tendencies
- Very high viscosity index for better lubrication and seal protection at extreme temperatures
- Excellent thermal and oxidative stability leading to longer fluid life and extended oil drain intervals
- Increased protection against rust, corrosion, carbon and varnish
- Very high flash points and auto-ignition points for added safety
- Non-toxic/non-hazardous

Applications

- Propane refrigeration compressor lubrication.
- Natural gas and other light hydrocarbon compressor applications.

Typical Properties*

Item	ArChine Propana RGI 68	
Appearance	Colorless clear liquid	
Density@20°C, g/cm ³	0.987	
Viscosity @ 40°C, mm ² /s	68.5	

Distributor Wanted

Tel: 86-21-64705533

Shanghai PingYiao Trading CO., Ltd. Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai 200235 P.R.China Telephone helpline: (86)15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com



Shanghai PingYiao Trading CO., Ltd.

	8 8 8	, .
Viscosity @100°C, mm ² /s	12.71	
Viscosity Index	187	
Flash Point(COC), °C	231	
Fire point, °C	249	
Pour Point, °C	-45	
Copper Corrosion, 100°C,3hr	1 grade	
Foam Characteristic, 24°C	25/0	
* The above data is typical data, not as	s product specifications.	



Distributor Wanted Tel: 86-21-64705533 Shanghai PingYiao Trading CO., Ltd. Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai 200235 P.R.China Telephone helpline: (86)15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com