

CPI Pale Oil Refrigeration Fluids 68

The CPI Pale Oil series refrigeration fluids are designed for use as cost effective fluids in general refrigeration applications.

The fluids are refined from carefully chosen wax free naphthenic crude oil basestocks to ensure the optimum quality product.

TYPICAL PROPERTIES	CPI PaleOil 68
Viscosity (cSt) @40°C	60.7
Viscosity (cSt) @100°C	7.0
@100°F	68.5
@210°F	7.2
Viscosity Index	65
Specific Gravity(@20°C)	0.905
Density (lbs/gal)	7.52
API Gravity ASTM D287	24.8
Moisture (ppm) ASTM D174	<50
Total Acid Number (mg KOH/g) ASTM D974	0.05
Flash Point(°F)ASTM D92	345
Fire Point (°F)ASTM D92	360
Pour Point (°F)ASTM D97	-40
Floc Point (°F)	-35
Aniline Point(°F)ASTM D611	200
Dielectric Strength (kV) ASTM D877	41.9
Sealed Glass Tube Test ANSI/ASHRAE 97	
R-12 Purity	98.9
R-22 Formation	1.1
Copper Strip Test ASTM D130	1a

Shanghai PingYiao Trading CO., Ltd.

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com

Shanghai PingYiao Trading CO., Ltd.

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com