

CPI Refrigeration Oil 32

CPI s are formulated from a premium selection of highly refined mineral oil basestocks to give a product with outstanding behavior in refrigeration systems.

Free of wax and other impurities , the CPI Refrigeration Oils have very good stability characteristics. They provide a wide range of use in many refrigeration applications. The CPI refrigeration oils are approved by several manufacturers under Calumet, RO series product.

TYPICAL PROPERTIES	Refrigeration Oil 32
Viscosity(cSt) ASTM D445@40°C	30.2
Viscosity(cSt) ASTM D445@100°C	4.4
@100°F	33.6
@210°F	4.5
Viscosity Index	122
Specific Gravity(@20°C)	0.890
Density (lbs/gal)	7.42
API Gravity	27.5
Moisture (ppm)ASTM D1744	<30
Total Acid Number(mg KOH/g)ASTM D974	0.05
Flash Point (°F)ASTM D92	350
Fire point(°F) ASTM D92	360
Pour Point(°F)ASTM D97	-50
Floc Point(°F)	-65
Aniline Point(°F)ASTM D611	183
Dielectric Strength (kV)ASTM D877	37.1
Sealed Glass Tube TestANSI/ASHRAE	99.9260.074
97R-12 PurityR-22 Formation	

Shanghai PingYiao Trading CO., Ltd.

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com

Shanghai PingYiao Trading CO., Ltd.

Shanghai PingYiao Trading CO., Ltd.

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com