

CPI Refrigeration Oil 46

CPI s are formulated from a premium selection of highly refined mineral oil basestocks to give a product with outstanding behavior in refrigeration systems. Free of wax and other impurities , the CPI Refrigeration Oils have very good stability characteristics. They provide a wide range of use in many refrigeration applications. The CPI refrigeration oils are approved by several manufacturers under Calumet, RO series product.

TYPICAL PROPERTIES

Refrigeration Oil 46

Viscosity(cSt) ASTM D445@40°C	43.0
Viscosity(cSt) ASTM D445@100°C	5.6
@100°F	48.2
@210°F	5.7
Viscosity Index	47
Specific Gravity(@20°C)	0.897
Density (lbs/gal)	7.49
API Gravity	26.2
Moisture (ppm)ASTM D1744	<30
Total Acid Number(mg KOH/g)ASTM D974	0.05
Flash Point (°F)ASTM D92	360
Fire point(°F) ASTM D92	370
Pour Point(°F)ASTM D97	-40
Floc Point(°F)	-55
Aniline Point(°F)ASTM D611	184
Dielectric Strength (kV)ASTM D877	40.3
Sealed Glass Tube TestANSI/ASHRAE	
97R-12 Purity	99.926

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.comE-mail: info@pingyiao.com

R-22 Formation	0.074
Copper Strip Test ASTM D130	1a

Shanghai PingYiao Trading CO., Ltd.

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com