

CP-4214-68

CP-4214 Series fluids are new technology refrigeration compressor lubricants. These proprietary fluids offer the advantages of excellent natural lubricity, excellent thermal and chemical stability with CFC refrigerants, a wide range of viscosity grades and solubility with certain refrigerants such as R-22 to very low temperatures. The availability of higher viscosity grades make these fluids an excellent choice for applications such as rotary screw compressors. A higher working viscosity allows for a better seal between rotors and provides better lubrication to bearings and seals. Good solubility at low temperatures assures lubricant return from flooded evaporators and better exchanger efficiency. Extremely low volatility provides improved lubricant / gas separation with coalescing filters.

Studies are currently in progress to examine potential energy savings in rotary screw compressors.

TYPICAL PROPERTIES*	CP-4214-68
Viscosity@40°C,cSt,ASTM D445	69.9
Viscosity @100°C,cSt	11.0
Viscosity @100°F	77.0
Viscosity @210°F	11.34
Viscosity Index ASTM D2270	148
Density, 1b/gal, 60°F	
Pour point °F (°C) ASTM D97	-25(-32)
Flash point C.O.C., °F (°C) ASTM D92	545(285)
Fire point C.O.C., °F (°C) ASTM D92	620(327)
Specific Gravity, ASTM D1298	0.982
Total Acid No., mg KOH/g, ASTM D664	<0.1

Shanghai PingYiao Trading CO., Ltd.

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com