

CP-4208-100**PRODUCT DESCRIPTION**

CP-4208-100 product is synthetic high temperature lubricants designed primarily for high temperature equipment such as oven chains and tenter frame ovens, as well as paint and ceramic curing ovens. Satisfactory performance can also be expected in applications involving bearing lubrication. Formulated from a quality synthetic basestock and additive system, CP-4208-100 product provide the following performance benefits.

- Excellent high temperature oxidation and thermal stability for prolonged lubricant life
- Extremely low volatility resulting in less oil consumption
- Superior antiwear properties for reduced chain drag

TYPICAL PROPERTIES*	CP-4208-100
Viscosity@40°C,cSt,ASTM D445	88
Viscosity @100°C,cSt	9.9
Viscosity @100°F	99.1
Viscosity @210°F	10.1
Viscosity Index ASTM D2270	90
Density, lb/gal, 60°F	8.14
Pour point °F (°C) ASTM D97	-40 (-40)
Flash point C.O.C., °F (°C) ASTM D92	540 (282)
Fire point C.O.C., °F (°C) ASTM D92	620 (327)
Specific Gravity, ASTM D1298	0.978

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.comE-mail: info@pingyiao.com