

CP-4208-220

PRODUCT DESCRIPTION

CP-4208-220 product is synthetic high temperature lubricants designed primarily for high temperature equipment such as oven chains and tender frame ovens, as well as paint and ceramic curing ovens. Satisfactory performance can also be expected in applications involving bearing lubrication. Formulated from a quality synthetic basestock and additive system, CP-4208-220 product provide the following performance benefits.

- Excellent high temperature oxidation and thermal stability for prolonged lubricant life
- Extremely low volatility resulting in less oil consumption
- Superior antiwear properties for reduced chain drag

TYPICAL PROPERTIES*	CP-4208-220
Viscosity@40°C,cSt,ASTM D445	217
Viscosity @100°C,cSt	16.4
Viscosity @100°F	250
Viscosity @210°F	16.9
Viscosity Index ASTM D2270	69
Density, lb/gal, 60°F	8.04
Pour point °F(°C) ASTM D97	-20 (-30)
Flash point C.O.C., °F(°C) ASTM D92	545 (285)
Fire point C.O.C., °F(°C) ASTM D92	580 (304)
Specific Gravity, ASTM D1298	0.965

Shanghai PingYiao Trading CO., Ltd.

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com