

CP-Paper Machine Oil 220

CP-Paper Machine Oil 220 has been developed with semisynthetic base oils and a carefully selected additive package to provide outstanding performance under severe operating conditions of high temperatures, high pressures and high levels of water encountered in the dry and wet end sections of paper machines.

Outstanding oxidation life and detergent dispersants maintain the cleanliness of critical machine components, such as dryer bearings. Excellent demulsibility allows water to drop out in a minimum of time allowing water-free oil to be recirculated. This oil is non-corrosive to copper alloys and affords excellent rust protection to ferrous metals.

TYPICAL PROPERTIES*

CP-Paper Machine Oil 220

Viscosity@40°C,cSt,	202.1
Viscosity @100°C,cSt	18.6
Viscosity Index ASTM D2270	102
Pour point, °C	-12
Flash point C.O.C., °C	270
Oxidation Stability, Hours to 2.0 TAN	5000

* These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com