

## CP-1078-150-F

CP-1078-150-F lubricant is custom-blended, hydrocracked isodewaxed base oil.

Primary benefits include:

Excellent thermal and oxidative stability

Superior corrosion protection

Reduced frictional drag for less downtime

Resistance to carbon and sludge build up

These high-performance lubricants prevent throw-off and dripping so they can adhere to metal surfaces in applications where oil control is critical to performance, e.g., textile mills and chain applications, as well as food processing applications.

Some CP-1078-F series products are approved for federally inspected meat and poultry plant applications with incidental food contact (H-1). Your local CPI representative can help you determine the appropriate product and viscosity for your needs.

### Preliminary product selection guide

Product name	Viscosity				
	@40°C cSt ASTM D445	@100°C cSt	@100°F	@210°F	Viscosity index ASTM D2270
CP-1078-150-F	149	15.3	785	81.5	104

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: [www.pingyiao.com](http://www.pingyiao.com)

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)