

CP-1518-150-F (Wanner C, D, E, F oil)

PRODUCT DESCRIPTION

CP-1518-150-F product is a unique custom blend of polyalkylene glycols with additives for oxidation stability, corrosion protection, metal deactivators and lubricity. The compatibility of these products with EPDM makes them excellent lubricants in EPDM diaphragm pump applications. Other advantages include stability, low ash content, and high viscosity index, shear stability, low solubility with many hydrocarbons and excellent lubricity.

CP-1518-F series products comply with FDA 21 CFR 178.3510–Lubricants with Incidental Food Contact.

TYPICAL PROPERTIES*

	CP-1518-150-F
Viscosity @ 40°C, cSt, ASTM D445	153.0
Viscosity @ 100°C, cSt	23.5
Viscosity @ 100°F, SUS	723
Viscosity @ 210°F, SUS	115.8
Viscosity Index, ASTM D2270	190
Density, lb/gal, 60°F, ASTM D4052	8.29
Pour Point °F (°C), ASTM D97	-30 (-34)
Flash Point, C.O.C., °F (°C), ASTM D92	500 (260)
Fire Point, C.O.C., °F (°C), ASTM D92	540 (282)
Specific Gravity, ASTM D4052	1.002

*These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com