

## CP-4608-1500-F

### PRODUCT DESCRIPTION

CP-4608-1500-F is a custom blended polyalphaolefin (PAO) synthetic hydrocarbon oil giving improved lubrication at high and low temperatures, reduced volatility, and compatibility with mineral oils and equipment designed for use with mineral oils.

Complies with FDA 21 CFR 178.3570 – Lubricants with Incidental Food Contact.

---

### **TYPICAL PROPERTIES\***

Viscosity @ 100°C ,cSt,ASTM D445.....	100
@ 40°C,cSt .....	1400
Viscosity Index, ASTM D2270.....	160
Pour Point , °F, (°C) ASTM D-97 .....	<-5 (<-20)
Flash Point, C.O.C., °F, (°C) ASTM D-92 .....	550(288)
Fire Point, C.O.C., °F (°C) ASTM D-92 .....	620(327)
Demulsibility , 10 minutes .....	40-39-1
Pump Wear, total ring and van weight loss, mg.	
ASTM 2882 .....	10
Foam Test, ASTM D892, Sequence I, II, III .....	Nil
Rust Prevention, ASTM D665, distilled water .....	Pass
Copper Strip Corrosion, Three hours	
At 212°F ,ASTM D130 .....	1
Specific Gravity, 60/60°F .....	0.852

\*These values are not intended for use in preparing specifications

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: [www.pingyiao.com](http://www.pingyiao.com)

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)