

CP-4608-220-F

Food Grade, Antiwear Lubricants

PRODUCT DESCRIPTION

CP-4608-F Series products are custom-blended polyalphaolefin (PAO) synthetic hydrocarbon oils giving improved lubrication at high and low temperatures, reduced volatility, and compatibility with mineral oils and equipment designed for use with mineral oils. They are formulated with additives for rust and oxidation inhibition and antiwear.

CP-4608-F Series products meet 21 CFR 178.3570 requirements for lubricants with the possibility of incidental food contact. Authorized by USDA for use in Federally inspected meat and poultry plants (H-1)

TYPICAL PROPERTIES*

CP-4608-220-F

Viscosity@40°C,cSt,ASTM D445	217.4
Viscosity @100°C,cSt	24.4
Viscosity @100°F	243.61
Viscosity @210°F	25.12
Viscosity Index ASTM D2270	141
Density 1b/gal, 60°F	7.05
Pour point°F (°C) ASTM D97	-46(-43)
Flash point C.O.C.,°F (°C) ASTM D92	535(279)
Fire point C.O.C.,°F (°C) ASTM D92	585(307)
Specific Gravity, ASTM D1298	0.846

* These values are not intended for use in preparing specifications

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com