

CP-4614-15-F

Food Grade, Chemical Process Lubricants

PRODUCT DESCRIPTION

CP-4614-F series products are custom-formulated synthetic hydrocarbon fluids giving improved lubrication at high and low temperatures, reduced volatility, and compatibility with mineral oils and equipment designed for use with mineral oils.

CP-4614-F series products are long life food grade lubricants specially processed for use as sealing fluids for chemical processing pumps, compressor lubricant/coolant, and other applications requiring improved chemical stability.

CP-4614-F series products meet 21 CFR 178.3570 requirements for lubricants with the possibility of incidental food contact. Authorized by USDA for use in federally inspected meat and poultry plants(H-1).

TYPICAL PROPERTIES*	CP-4614-15-F
Viscosity@40°C,cSt, ASTM D445	16.8
Viscosity @100°C,cSt	3.8
Viscosity @100°F	18.2
Viscosity @210°F	3.9
Viscosity Index ASTM D2270	120
Density 1b/gal, 60°F	6.82
Pour point °F (°C) ASTM D97	-98(-72)
Flash point C.O.C., °F (°C) ASTM D92	432(222)
Fire point C.O.C., °F (°C) ASTM D92	478(248)
Specific Gravity,ASTM D1298	0.818

* These values are not intended for use in preparing specifications

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com