

CP-4614-68-F

Food Grade, Chemical Process Lubricants

PRODUCT DESCRIPTION

CP-4614-F series products are custom-formulated synthetic hydrocarbon fluids giving improved lubrication at high and low temperatures, reduced volatility, and compatibility with mineral oils and equipment designed for use with mineral oils.

CP-4614-F series products are long life food grade lubricants specially processed for use as sealing fluids for chemical processing pumps, compressor lubricant/coolant, and other applications requiring improved chemical stability.

CP-4614-F series products meet 21 CFR 178.3570 requirements for lubricants with the possibility of incidental food contact. Authorized by USDA for use in federally inspected meat and poultry plants(H-1).

| TYPICAL PROPERTIES* | CP-4614-68-F |
|--------------------------------------|---------------------|
| Viscosity@40°C,cSt, ASTM D445 | 62.9 |
| Viscosity @100°C,cSt | 9.6 |
| Viscosity @100°F | 69.5 |
| Viscosity @210°F | 9.8 |
| Viscosity Index ASTM D2270 | 137 |
| Density 1b/gal, 60°F | 6.98 |
| Pour point °F (°C) ASTM D97 | -63(-53) |
| Flash point C.O.C., °F (°C) ASTM D92 | 519(268) |
| Fire point C.O.C., °F (°C) ASTM D92 | 568(298) |
| Specific Gravity,ASTM D1298 | 0.835 |

* These values are not intended for use in preparing specifications

Shanghai PingYiao Trading CO., Ltd.

Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com