

# ArChine Gascomp GHT 32

## Semi-Synthetic Hydrocarbon Gas Compressor Oil

ArChine Gascomp GHT 32 is custom-blended, highly refined, semi-synthetic lubricant. This product provides excellent wear protection as well as enhanced resistance against oxidation, rust, corrosion and carbon buildup.

#### Features

- Excellent oxidation stability
- High film strength
- Reduced downtime and maintenance costs •
- Outstanding fluid life
- Reduced lubricant consumption ۲

#### **Application:**

Tradine CO ArChine Gascomp GHT 32 is widely used for applications where lubricants give negligible solubility in contact with hydrocarbon gas. It is also recommended for use in harsh chemical environments and sour hydrocarbon (H2S) gas systems.

### **Typical Physical Properties\***

Properties	ArChine Gascomp GHT 32
Appearance	Light yellow, clear liquid
Density, 20°C g/cm3	0.861
Viscosity@ $40^{\circ}$ C, mm <sup>2</sup> /s	32.2
Viscosity@100°C, mm <sup>2</sup> /s	5.40
Viscosity Index	101
Flash Point(open cup), °C	214
Fire Point, °C	236
Pour Point, °C	-18

#### **Distributor Wanted**

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533 Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai 200235 P.R.China Telephone helpline: (86)15900706965 Fax: 86-21-64705533-209 Website: www.pingyiao.com E-mail: info@pingyiao.com



	Copper Strip Test,	100°C, 3	hr	1
--	--------------------	----------	----	---

\*The above data is typical data, not as product specifications.

shandbhai Pines iao Tradines o,

#### **Distributor Wanted**

Shanghai PingYiao Trading CO., Ltd.Tel: 86-21-64705533Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District , Shanghai200235 P.R.ChinaTelephone helpline: (86)15900706965Fax: 86-21-64705533-209Website: www.pingyiao.comE-mail: info@pingyiao.com