

## **CP-1000-150**

### **PRODUCT DESCRIPTION**

CP-1000-150 product is custom-blended highly refined, chemically inert lubricants. Silicone additions act as a lubricity improver, defoamant, pour point depressant and help protect the metal surfaces against corrosion. Polyalphaolefin (PAO) synthetic hydrocarbon additions act as a stable viscosity improver. Widely used for applications in the chemical processing industries where the lubricant is subjected to harsh chemical environments and certain applications (e.g. flooded rotary screw compressors) where the PAO is needed to improve shear stability and compensate for thinning of the lubricant by the compressed gas.

### **APPLICATIONS**

Lubricants/coolant for process and gas rotary screw compressors.

Lubricant and sealing fluid for rotary mechanical shaft seals of chemical processing pumps and agitated kettles.

Crankcase and cylinder lubricant for reciprocating compressors handling chemical gases (i.e. HCl and MeCl gases)

Lubricant for vacuum pumps handling chemical vapors.

<b>TYPICAL PROPERTIES**</b>	<b>CP-1000-150</b>
Viscosity @ 40°C, cSt, ASTM D445	140
Viscosity @ 100°C, cSt	17.0
Viscosity @ 100°F, SUS	632
Viscosity @ 210°F, SUS	86.0
Viscosity Index ASTM D2270	136
Density, lb/gal, 60°F	7.17
Pour Point °F (°C) ASTM D97	<-20(-29)
Flash Point, C.O.C °F (°C) ASTM D92	450(232)
Fire Point, C.O.C °F (°C) ASTM D92	500(260)
Specific Gravity, ASTM D1298	0.86

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: [www.pingyiao.com](http://www.pingyiao.com)

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)

\*These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Shanghai PingYiao Trading CO., Ltd.

Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: [www.pingyiao.com](http://www.pingyiao.com)

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)