

CP-1005-220

PRODUCT DESCRIPTION

CP-1005-220 product is custom-blended, highly refined, dewaxed, chemically inert lubricants. Silicone additions act as a lubricity improver, defoamant, pour point depressant and help protect the metal surfaces against corrosion. Widely used for applications where the lubricant is subjected to harsh Chemical environments. Contains an additive compatible with sour hydrocarbon (H₂S) gas systems

APPLICATIONS

Lubricants/coolant for process and gas screw compressors.

Lubricant/coolant for process applications. Especially effective in combating corrosion and promoting long life in sour hydrocarbon gas compressor.

TYPICAL PROPERTIES**

CP-1005-220

Viscosity @ 40°C, cSt , ASTM D445	215
Viscosity @ 100°C ,cSt	19.5
Viscosity @ 100°F , SUS	1130
Viscosity @210°F , SUS	98.9
Viscosity Index ASTM D2270	103
Density, 1b/gal, 60°F	7.4
Pour Point °F (°C) ASTM D97	-35(-37)
Flash Point, C.O.C °F (°C) ASTM D92	490(254)
Fire Point, C.O.C °F (°C) ASTM D92	530(276)
Specific Gravity, ASTM D1298	0.89

** These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com