

CP-1010-150

PRODUCT DESCRIPTION

CP-1010 Series lubricants are custom blended, highly refined, chemically resistant lubricants. New state of the art additives greatly increase the protection of compressors from hydrogen sulfide (H₂S) corrosion. CP-1010 offers excellent lubricity and foam control, as well as low pour points.

This product is widely used in flooded rotary screw compressors in gas gathering environments where shear stability, lubricity and resistance to chemical attack by the compressed gas are required.

The CP-1010 series does not contain compressor fouling additives such as detergents, viscosity improvers, or highly reactive components.

APPLICATIONS

- Lubricant/coolant for process and hydrocarbon gas rotary screw and reciprocating compressors.
- Proprietary additives help to protect metal surfaces from corrosive attack by sour gas hydrogen sulfide (H₂S).

Your local CPI representative can help you determine the appropriate product and viscosity for your needs.

All CPI lubricants are Kosher, Pareve, and Halal registered.

TYPICAL PROPERTIES

Viscosity, @40°C,cSt,ASTM D445	154
Viscosity, @100°C,cSt	15.9
Viscosity Index, ASTM D2270	107
Pour Point °F (°C) , ASTM D97	-22 (-30)
Flash Point °F (°C) , ASTM D92	500 (260)
Tri-Phase Acid Corrosion Test Modified ,ASTM D665	PASS

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207,Yinhai Building, No.250,Caoxi Road,Xuhui District, Shanghai

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com

--	--

Shanghai PingYiao Trading CO., Ltd.

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yinhai Building, No.250, Caoxi Road, Xuhui District, Shanghai

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com