

CP-1505-320

PRODUCT DESCRIPTION

The CP-1505-320 product is unique co-polymer of polyalkylene glycols. The ability of these lubricants to limit dilution by hydrocarbon gas is particularly advantageous in flooded screw compressors. Other advantages include stability, low ash content, high viscosity index, shear stability, and excellent lubricity.

CP-1505-220 products is not recommended for use in systems where oxygen and water are present.

APPLICATIONS

- Rotary screw, reciprocating and rotary screw compressors operating on hydrocarbons where oxygen and water are not present.
- Hydrocarbon refrigeration compressors.
- Ammonia soluble refrigeration lubricant.

TYPICAL PROPERTIES*	CP-1505-320
Viscosity@40°C, cSt, ASTM D445	305.2
Viscosity@100°C, cSt	59.1
Viscosity@100°F, SUS	1529
Viscosity@210°F, SUS	282
Viscosity Index ASTM D2270	262
Density, lb/gal, 60°F	8.84
Pour Point °F (°C) ASTM D97	-28(-33)
Flash Point, C.O.C., °F (°C) ASTM D92	500(260)
Fire Point, C.O.C., °F (°C) ASTM D92	550(288)
Specific Gravity, ASTM D1298	1.06

**These values are not intended for use in preparing specifications

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com