

CP-1505-68

PRODUCT DESCRIPTION

The CP-1505-68 product is unique co-polymer of polyalkylene glycols. The ability of these lubricants to limit dilution by hydrocarbon gas is particularly advantageous in flooded screw compressors. Other advantages include stability, low ash content, high viscosity index, shear stability, and excellent lubricity.

CP-1505-68 products is not recommended for use in systems where oxygen and water are present.

APPLICATIONS

- Rotary screw, reciprocating and rotary screw compressors operating on hydrocarbons where oxygen and water are not present.
- Hydrocarbon refrigeration compressors.
- Ammonia soluble refrigeration lubricant.

TYPICAL PROPERTIES*	CP-1505-68
Viscosity@40°C, cSt, ASTM D445	66.8
Viscosity@100°C, cSt	14.1
<hr/>	
Viscosity@100°F, SUS	335
Viscosity@210°F, SUS	75.6
Viscosity Index ASTM D2270	221
Density, lb/gal, 60°F	8.75
Pour Point °F (°C) ASTM D97	70.6(57)
Flash Point, C.O.C., °F (°C) ASTM D92	440(226)
Fire Point, C.O.C., °F (°C) ASTM D92	465(240)
Specific Gravity, ASTM D1298	1.050

**These values are not intended for use in preparing specifications

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com