

ArChine Gascomp HGI 32

Hydrocarbon Gas Compressor Oil

Product Description

ArChine Gascomp HGI 32 is unique custom blend of polyalkylene glycols with additives for oxidation stability, corrosion protection and lubricity. ArChine Gascomp HGI 32 is formulated to give negligible solubility or dilution in contact with hydrocarbon liquids or vapors.

Product Features

- ◆ Highly resistant to oxidation and thermal degradation
- ◆ Excellent corrosion protection
- ◆ Shear stability
- ◆ Excellent lubricity for reduced friction and wear
- ◆ Low ash content
- ◆ Reduced spalling, pitting, and wear

Applications

- ◆ Flooded rotary screw compressors
- ◆ Reciprocating compressors
- ◆ Hydrocarbon gas compressors

Typical Physical Properties

Properties	ArChine Gascomp HGI 32
Appearance	Light yellow, clear liquid
Density, 20°C g/cm ³	0.980
Viscosity, 40°C mm ² /s	33.7
Viscosity, 100°C mm ² /s	6.60
Viscosity Index	155
Flash Point (Open cup, °C)	262

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com

ARCHINE

Shanghai PingYiao Trading CO., Ltd.

Fire Point, °C	280
Pour Point, °C	-48
Copper Strip Test, 100°C, 3hr, grade	1
Foaming, 24°C	15/0
93.5°C	10/0
24°C	15/0

* The above data is typical data, not as product specifications.

Distributor Wanted

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com