

CP-1507-22

PRODUCT DESCRIPTION

CP-1507-22 product is polyalkylene glycol lubricants, formulated to give negligible solubility or dilution in contact with hydrocarbon liquids or vapors. The ability of these lubricants to withstand dilution by hydrocarbon gases is particularly advantageous in liquid ring vacuum pump and centrifugal compressors handling high concentrations of hydrocarbon and gasoline vapors.

CP-1507-22 is a heat stable polymer in the absence of oxygen. They are soluble in water.

TYPICAL PROPERTIES*

CP-1507-22

Viscosity@40 °C,cSt,ASTM D445	23.89
Viscosity@100 °C,cSt	4.92
Viscosity@100°F, SUS	123.6
Viscosity@210°F,SUS	42.7
Viscosity Index ASTM D2270	131
Density, lb/gal, 60°F	9.33
Density, lb/gal 100°F(40 °C)	--
Density, lb/gal 150°F(66 °C)	--
Density, lb/gal 200°F(93 °C)	--
Pour Point °F(°C)ASTM D97	-54.4(-48)
Flash Point, C.O.C., °F(°C)ASTM D92	355(179)
Fire Point, C.O.C., °F(°C)ASTM D92	360(182)
Specific Gravity, ASTM D1298	1.120

**These values are not intended for use in preparing specifications

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com