

## **ArChine Gascomp WSG 22**

### **Water soluble Hydrocarbon Gas Compressor Oil**

ArChine Gascomp WSG 22 is polyalkylene glycol lubricant, formulated to give negligible solubility or dilution in contact with hydrocarbon liquids or vapors.

Primary benefits include:

- Thermal stability
- Insoluble in hydrocarbon gas
- Resist dilution for stable viscosity
- Water soluble

This high-performance lubricant is recommended for use in:

- Liquid ring vacuum pumps
- Centrifugal compressors
- Flooded rotary screw compressors

#### **Typical Physical Properties\***

<b>Properties</b>	<b>ArChine Gascomp WSG 22</b>
Appearance	Light yellow, clear liquid
Viscosity@ 40°C, mm <sup>2</sup> /s	23.54
Viscosity@100°C, mm <sup>2</sup> /s	5.30
Viscosity Index	168
Flash Point(open cup), °C	170
Fire Point, °C	190
Pour Point, °C	-57
Copper Strip Test, 100°C, 3hr	1
Foaming, 24°C	15/0

\*The above data is typical data, not as product specifications.

#### **Distributor Wanted**

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai  
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: [www.pingyiao.com](http://www.pingyiao.com)

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)