

CP-1508-68

PRODUCT DESCRIPTION

CP-1508-68 product is polyalkylene glycol lubricants, formulated to give negligible solubility or dilution in contact with hydrocarbon liquids or vapors. The ability of these lubricants to withstand dilution by hydrocarbon gases is particularly advantageous in liquid ring vacuum pump and compressors handling high concentrations of hydrocarbon and gasoline vapors. CP-1508-68 product is soluble in water.

CP-1508-68 product is a heat stable polymer containing rust and oxidation inhibitors, antiwear and mild boundary lubrication additives to help prevent corrosion where hydrogen sulfide (H₂S) is present.

TYPICAL PROPERTIES*	CP-1508-68
Viscosity@40°C,cSt,ASTM D445	67.45
Viscosity@100°C,cSt	9.47
<hr/>	
Viscosity@100°F,cSt	74.92
Viscosity@210°F,cSt	9.71
Viscosity Index ASTM D2270	119
Density, lb/gal, 60°F	9.27
Pour Point °F(°C)ASTM D97	-55(-48)
Flash Point, C.O.C., °F(°C)ASTM D92	445(229)
Fire Point, C.O.C., °F(°C)ASTM D92	480(249)

**These values are not intended for use in preparing specifications

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com