

**ArChine Gascomp WSG 150****Water soluble Hydrocarbon Gas Compressor Oil**

ArChine Gascomp WSG 150 is polyalkylene glycol lubricant, formulated to give negligible solubility or dilution in contact with hydrocarbon liquids or vapors.

Primary benefits include:

- Thermal stability
- Insoluble in hydrocarbon gas
- Resist dilution for stable viscosity
- Water soluble

This high-performance lubricant is recommended for use in:

- Liquid ring vacuum pumps
- Centrifugal compressors
- Flooded rotary screw compressors

**Typical Physical Properties\***

Properties	ArChine Gascomp WSG 150
Appearance	Light yellow, clear liquid
Density, 20°C, g/cm <sup>3</sup>	1.044
Viscosity@ 40°C, mm <sup>2</sup> /s	150.8
Viscosity@100°C, mm <sup>2</sup> /s	28.28
Viscosity Index	227
Flash Point(open cup), °C	258
Fire Point, °C	278
Pour Point, °C	-33
Copper Strip Test, 100°C, 3hr	1
Foaming, 24°C	10/0

\*The above data is typical data, not as product specifications.

**Distributor Wanted**

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: A1207, Yin Hai Building, No.250, Caoxi Road, Xuhui District, Shanghai  
200235 P.R.China

Telephone helpline: (86)15900706965

Fax: 86-21-64705533-209

Website: [www.pingyiao.com](http://www.pingyiao.com)

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)