

CP-1528-32

PRODUCT DESCRIPTION

CP-1528-32 product is unique co-polymers of polyalkylene glycols. The ability of these lubricants to withstand dilution by hydrocarbon and other compressed gas is particularly advantageous in flooded screw compressors. Other advantages include stability, low ash content, high viscosity index; shear stability, low solubility with many hydrocarbons and excellent lubricity.

CP-1528-32 product is insoluble with water at temperatures above 160°F, and are fortified with rust and oxidation inhibitors. They also contain antiwear and mild boundary lubrication additives.

TYPICAL PROPERTIES*

CP-1528-32

| | |
|---------------------------------------|----------|
| Viscosity @ 40°C cst ASTM D445 | 33.8 |
| Viscosity @ 100°C cst | 7.4 |
| Viscosity @ 100°F | 36.5 |
| Viscosity @ 210°F | 7.6 |
| Viscosity Index ASTM D2270 | 194 |
| Density, lb/gal, 60°F | 8.58 |
| Pour Point °F (°C) ASTM D97 | -78(-71) |
| Flash Point, C.O.C., °F (°C) ASTM D92 | 410(210) |
| Fire Point, C.O.C., °F (°C) ASTM D92 | 475(246) |
| Specific Gravity, ASTM D1298 | 1.029 |

*These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com