

CP-9000-46**Custom Blended Oil****PRODUCT DESCRIPTION**

CP-9000 series products are custom blended highly refined base fluids with additives to produce a premium, extended life, rust and oxidation-inhibited lubricant. They are formulated to give good demulsibility and antifoam properties. CP-9000 series products also have excellent lubricity and antiwear characteristics.

APPLICATIONS

CP-9000 series products are premium lubricants formulated for oil circulating systems such as rotary screw air compressors and hydraulic applications requiring antiwear. The conventional mineral oils commonly used in rotary screw air compressors.

TYPICAL PROPERTIES*	CP-9000-46
Viscosity@40°C, cSt, ASTM D445	43.46
Viscosity@100°C, cSt,	6.65
Viscosity@100°F	48.1
Viscosity@210°F	6.8
Viscosity Index ASTM D2270	105
Density, lb/gal, 60°F	7.08
Pour point °F (°C) ASTM D97	-27 (-33)
Flash point C.O.C. °F (°C) ASTM D92	432 (222)
Fire point C.O.C. °F (°C) ASTM D92	445 (229)
Specific Gravity, ASTM D1298	0.85

*These Values are not intended for use in preparing specifications

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com