

Shanghai PingYiao Trading CO., Ltd.

CP-9001-22

PRODUCT DESCRIPTION

CP-9001 series products are custom formulated lubricants specifically designed for long life under the severe, demanding conditions encountered in recirculating systems such as liquid ring vacuum pumps and rotary screw compressors.

CP-9001 series products are based on highly refined, hydrotreated dewaxed paraffinic oil.

This special refining coupled with state of the art additive technology results in performance improvements beyond other mineral oils. Among these are:

Exceptional oxidative stability	Long life
---------------------------------	-----------

Less frictional drag

Less down time

Low evaporation loss Improved performance

Viscosity stability Improved economy

Thermal & hydrolytic stability Consistent quality

Lower equipment maintenance Rust and corrosion inhibited

Resistance to carbon buildup and low sludging tendency

Authorized by USDA for use in federally inspected meat and poultry plants with no possibility of food contact (H-2)

TYPICAL PROPERTIES**	CP-9001-22
Viscosity @ 40°C,cSt, ASTM D445	21.5
Viscosity @ 100℃, cSt	4.25
Viscosity @ 100°F	23.55
Viscosity @210°F	4.4
Viscosity Index ASTM D2270	100
Density, 1b/gal, 60°F	7.1
Pour Point °F (°C) ASTM D97	-40(40)

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533

Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250 Telephone helpline: 15900706965 Fax: 86-21-64705533-209

Website: www.pingyiao.com
E-mail: info@pingyiao.com



Shanghai PingYiao Trading CO., Ltd.

365(185) Flash Point, C.O.C °F (°C) ASTM D92

385(196) Fire Point, C.O.C °F (°C) ASTM D92

0.852 Specific Gravity, ASTM D1298

** These values are not intended for use in preparing specifications.

Shanghai Ping Viao Frading

Shanghai PingYiao Trading CO., Ltd. Tel: 86-21-64705533

Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250 Telephone helpline: 15900706965 Fax: 86-21-64705533-209

Website: www.pingyiao.com E-mail: info@pingyiao.com