

JICHUAN 4T RACER OIL,

JASO MA

HEAVY DUTY MULTI-GRADE MOTORCYCLE OIL API SG

PRODUCT DESCRIPTION:

JICHUAN 4T RACER OIL is manufactured from panaffinic, high viscosity index base oils They contain detergent dispersant, oxidation-corrosion inhibitors and VI improvers. Provides cold cranking characteristics and protects engines over a wide range of climatic conditions.

TYPICAL USES:

• Recommended for all 4-cycle motorcycle and small engine applications.

- All major motorcycle manufacturers requiring SG motor oils.
- API Service SG.

Meets or exceeds 4-cycle engine manufacturers specifications for

lawnmowers, Briggs & Stratton, Clinton Craftsman, Kawasaki, Kohler, Onan, Tecumseh Wisconsin.

• All chain saws requiring 4-cycle SG oils.

FEATURES:

• Keeps engines cleaner - specifically formulated to help prevent engine deposits.

- Meets and exceeds motorcycle manufacturers warranty.
- Protects against rust.

• Reduces engine wear with effective anti-wear agents which protect cam shaft lobes and hydraulic lifters.

• Provides high temperature protection through use of effective oxidation inhibitors.

• Compatible - can be mixed safely with other high quality motor oils.

• Special additives help reduce scuffing, ring sticking, foaming, and engine wear under high temperature conditions.

• JASO MA "on File" status

GRADES.SAE	10W-30	10W-40	20W-50		
GRAVITY,°API	31.4	31.3	30.2		
FLASH POINT,°F.	430	440	455		
FIRE POINT,°F.	460	470	480		

TYPICAL INSPECTIONS

Shanghai Jichuan Trading Co.,Ltd.

Add:No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai24h Hotline:15900706965Fax:(86)021-64513829Website:www.pingyiao.comE-mail:info@jichuan.sh.cn

Tel: (86)021-64820099

JiChuan Shanghai Jichuan Trading						
POUR POINT,°F.	-15	-15	-5			
VISCOSITY:						
SUS@100°F.	355	418	796			
SUS@210°F.	67.2	74.9	102.6			
cSt@40°C.	69.9	82.3	154.7			
cSt@100°C.	11.9	13.9	20.4			
VISCOSITY INDEX	166	175	153			
COLOR,D-1500	4.0	4.0	4.0			
SULFATED ASH WT.	1.02	1.02	1.02	~		
%				\bigcirc \bigcirc \circ		

0.13

8.1

0.13 8.1

.

Grandhai tichtan Shandhai VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

0.13

8.1

ZINC,WT.%

TBN,D-2896

Shanghai Jichuan Trading Co., Ltd. Add: No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai 24h Hotline: 15900706965 Fax: (86)021-64513829 Website: www.pingyiao.com E-mail: info@jichuan.sh.cn

Tel: (86)021-64820099