

JICHUAN GT-21 XT MOTOR OIL

HEAVY DUTY CRANK CASE OILS FOR FLEET & CONSTRUCTION
EQUIPMENT ENGINES - API-SG/CC

PRODUCT DESCRIPTION:

JICHUAN GT-21 XT MOTOR OIL is manufactured from paraffinic high viscosity index base oils. They contain detergent dispersant, oxidation-corrosion inhibitors and VI improvers. All grades provide cold cranking characteristics and give engine protection over a wide range of climatic conditions.

TYPICAL USES:

JICHUAN GT-21 XT MOTOR OIL meets or exceeds these performance requirements:

- API Service Classification SG/CC.
- US Military Specifications Mil-L-46152B, Mil-L-2104A (obsolete) and Supplement I (obsolete).
- Ford M2C101C, M2C157A and M2C153B.
- General Motors, GM6048M, GM6049M, and GM60Y5M (SAE 10W-30).
- European auto makers ACEA
- Daimler-Benz
- Meets warranty requirements of American Motors, Chrysler, Ford, General Motors and other manufacturers.
- Hydraulic Fluid & Transmission Fluid where multigrade oils are recommended.

Note: Oxidation inhibitors contain copper and should be considered if oil analysis is used (see below).

FEATURES:

- Keeps engines cleaner-specifically formulated to help prevent engine deposits and keep PCV valves operating properly.
- Meets and exceeds car manufacturers warranty.
- Protects against rust.
- Reduces engine wear with effective anti-wear agent; which protects cam shaft lobes and hydraulic lifters.
- Provides high temperature protection through use of effective oxidation inhibitors.
- Compatible - can be mixed safely with other high quality motor oils.
- Grade 5W-30 meets and exceeds U.S. car makers SG warranty



requirements.

TYPICAL INSPECTIONS

GRADES,SAE	5W-30	10W-30	10W-40	15W-40	15W-50	20W-50
GRAVITY,°API	30.1	29.9	30.5	27.0	28.5	27.2
FLASHPOINT,°F.	420	430	430	450	440	410
FIREPOINT,°F.	440	480	480	500	490	490
POURPOINT,°F.	-35	-15	-15	-5	-5	-5
VISCOSITY:						
SUS@100°F.	319	383	488	500	739	837
SUS@210°F.	63.7	65.2	78.3	74.8	94.3	92
cSt@40°C.	62.8	74.87	95.7	97.5	143.4	160.8
cSt@100°C.	11.0	11.36	14.7	13.84	18.5	17.94
VISCOSITYINDEX	159	144	160	143	145	123
COLOR,D-1500	4.0	4.5	4.5	4.5	4.5	4.5
SULFATEDASH,WT	0.7	0.7	0.7	0.7	0.7	0.7
ZINC,WT.%	0.09	0.09	0.09	0.09	0.09	0.09
TBN,D-2896	5.5	5.5	5.5	5.5	5.5	5.5

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Fax: (86)021-64513829

E-mail: info@jichuan.sh.cn

Tel: (86)021-64820099