

## JICHUAN TROPICAL SYN TURBO

A SUPER-PREMIUM GASOLINE ENGINE OIL MEETING API SERVICE API  
SJ / CE

### PRODUCT DESCRIPTION:

JICHUAN TROPICAL SYN TURBO MOTOR OIL is a gasoline engine oil designed to meet the warranty requirements of most gasoline engine manufacturers and was specifically developed to be a "universal" engine oil recommended for both diesel engines as well as gasoline engines. It is suitable over a wide range of operating service and temperature conditions. This highly fuel efficient lubricant delivers improved mileage under all conditions. The balanced system of additives in combination with new generation synthetics is the finest pollution avoidance lubricant available anywhere. With a high operating viscosity, this product will deliver superior lubrication under all conditions.

### TYPICAL USES:

- JICHUAN TROPICAL SYN TURBO MOTOR OIL exceeds API Service Classification API SJ / CE performance requirements and is recommended for domestic and foreign high performance gasoline engines – especially recommended for turbo-charged and small 4-cylinder high RPM engines.
- Also recommended for use in automotive diesel engines.
- Foreign Cars - Meets & exceeds warranty requirements of most of the foreign cars exceeding API SJ / CE specification.

### FEATURES:

- Out performs all conventional premium motor oils.
- Optimum protection for hot running, turbo-charged, gasoline and diesel engines.
- Allows high mileage change between oil changes.
- Compatible with conventional oils.
- Wide range temperature performance.

### TYPICAL INSPECTIONS

GRADES,SAE	ASTMTest	10W-40	10W-50
GRAVITY,°API	D-287	30.6	30.8
FLASH POINT,°F.	D-92	435	440
FIRE POINT,°F.	D-92	480	470

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: [www.pingyiao.com](http://www.pingyiao.com)

Fax: (86)021-64513829

E-mail: [info@jichuan.sh.cn](mailto:info@jichuan.sh.cn)

Tel: (86)021-64820099



# Shanghai Jichuan Trading

POUR POINT,°F.	D-97	-25	-20
VISCOSITY:			
cSt@40°C.	D-445	112	134
cSt@100°C.	D-445	14.84	20
VISCOSITY INDEX	D-2270	140	145
COLOR,D-1500	3.5	3.5	
SULFATED ASH,WT. %	D-874	0.9	0.9
ZINC,WT. %	0.13	0.13	
TBN,D-2896	D-2896	8.0	8.0

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: [www.pingyiao.com](http://www.pingyiao.com)

Fax: (86)021-64513829

E-mail: [info@jichuan.sh.cn](mailto:info@jichuan.sh.cn)

Tel: (86)021-64820099