

JICHUAN EPAX HP

HIGH FILM STRENGTH, HEAVY DUTY E.P. GEAR OIL

JICHUAN EPAX HP is a sulfur-phosphorus type gear lubricant exceeding the requirements of API Service Classification GL-5. Manufactured from premium quality high VI, paraffin base oil fortified with rust and corrosion inhibitor, extreme pressure anti-wear additive and pour point depressant.

TYPICAL USES:

- Exceeds API Service Quality GL-5.
- Mil-L-2105D Performance Level.
- Mack Specification GO-G.
- Clings to the gear sets.
- Recommended for differentials and conventional transmissions in passenger cars and trucks where GL-5 type lubricant is specified.
- Suitable for industrial reduction gears where EP type oils are required.
- Suitable as make-up in limited slip differentials.

FEATURES:

- Extra high film strength.
- Protects hypoid gears from wear and scuffing.
- Has exceptional thermal and oxidative stability to resist sludging.
- Provides rust protection to gears.
- Multi-viscosity provides year round use.

TYPICAL INSPECTIONS

GRADE,SAE	90	140	80W-90	85W-140
GRAVITY,°API	25.4	24.3	26.0	23.4
FLASHPOINT,°F.	400	420	395	410
FIREPOINT,°F.	430	460	420	445
POURPOINT,°F.	5	10	-25	6
VISCOSITY:				
SUS@100°F.	1214	2820	903	1853
SUS@210°F.	98	155	85	126
cSt@40°C.	229.2	523	171.7	347
cSt@100°C.	19.2	31.65	16.26	25.5
VISCOSITYINDEX	95	90	98	25.5
COLOR,D1500	4.0	4.5	3.5	5.0

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Tel: (86)021-64820099

Fax: (86)021-64513829

E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

BROOKFIELD@26°C.CPS	-	-	90,000	-
BROOKFIELD@12°C.CPS	-	-	-	85,000

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

Contains advanced high performance additive chemistry

Shanghai Jichuan Trading Co., Ltd.

Shanghai Jichuan Trading Co., Ltd.

Add: No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai

Tel: (86)021-64820099

24h Hotline: 15900706965

Fax: (86)021-64513829

Website: www.pingyiao.com

E-mail: info@jichuan.sh.cn