

JICHUAN EPAX-G5 XT

HIGH FILM STRENGTH, HEAVY DUTY E.P. RED TAC GEAR OILS

PRODUCT DESCRIPTION:

JICHUAN EPAX G-5 XT is a sulfur-phosphorus type gear lubricant exceeding the requirements of API Service Classification GL-5. Manufactured from premium quality high VI, paraffin base oil fortified with a tackiness agent, rust and corrosion inhibitor, extreme pressure anti-wear additive, pour point depressant and foam inhibitors.

TYPICAL USES:

- Exceeds API Service Quality GL-5 & proposed GL-7, GL-8
- Mil-L-2105D Performance Level.
- Mack Specification GO-G.
- Recommended for differentials and conventional transmissions in passenger cars and trucks where GL-5 type lubricant is specified.
- Suitable for industrial reduction gears where EP type oils are required.
- Suitable as make-up in limited slip differential

FEATURES:

- Tackiness agent to cling to the gear sets.
- Extra high film strength.
- Protects hypoid gears from wear and scuffing.
- Has exceptional thermal and oxidative stability to resist sludging.
- Provides rust protection to gears.
- Multi-viscosity provides year round use.
- Non-foaming.
- Distinct red color for easy identification & leak detection.

TYPICAL INSPECTIONS

GRADE,SAE	90	140	80W-90	85W-140
GRAVITY,°API	25.4	24.3	26.0	23.4
FLASH POINT,°F.	400	420	395	410
FIRE POINT,°F.	430	460	420	445
POUR POINT,°F.	5	10	-25	6
VISCOSITY:				
SUS@100°F.	1214	2820	903	1853
SUS@210°F.	98	155	85	126
cSt@40°C.	229	523	172	347

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Fax: (86)021-64513829

E-mail: info@jichuan.sh.cn

Tel: (86)021-64820099



Shanghai Jichuan Trading

cSt@100°C.	19.2	31.7	16.3	25.5
VISCOSITYINDEX	95	90	98	96
COLOR	RED	RED	RED	RED
BROOKFIELD@-26°C.CPS	-	-	90,000	-
BROOKFIELD@-12°C.CPS	-	-	-	85,000

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

Shang Jichuan Trading Co., Ltd.

Shanghai Jichuan Trading Co., Ltd.

Add: No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Fax: (86)021-64513829

E-mail: info@jichuan.sh.cn

Tel: (86)021-64820099