

JICHUAN SYN EPAX G5 PLUS

SUPER-PREMIUM VERSATILE EXTRA HEAVY DUTY GEAR LUBRICANT -
GL-5 PLUS

PRODUCT DESCRIPTION:

JICHUAN SYN EPAX G5 PLUS is a multi-purpose sulfur-phosphorus type hypoid gear lubricant exceeding requirements of API Service Classification GL-5. It is manufactured from highest quality base oils fortified with VI improvers, rust inhibitors, foam suppressants, anti-wear and extreme pressure additives and pour point depressants. The multi-viscosity grades may be used over wide temperature ranges.

TYPICAL USES:

- Exceeds API GL-5.
- Exceeds Military Specification Mil-L-2105D.
- Exceeds Mack Specifications GO-F, GO-G & GO-H
- Rockwell Specification 0-76A and 0-76D.
- Recommended for differentials and conventional transmissions in passenger cars and trucks where GL-5 fluids are specified.
- Suitable for industrial reduction gears where EP type oils are required.
- Suitable as make-up in limited slip differentials (Factory specified lubricant required on complete refill of new or rebuilt units.)
- High performance European automobiles.

FEATURES:

- Exceptional thermal and oxidative stability to protect pans and ensure maximum performance
- Allows start up at extremely low temperatures.
- Protects hypoid gears from wear and scuffing.
- Provides rust protection to gears.
- Multi-purpose for minimum inventory.
- Multi-viscosity provides year round use.
- Non-foaming.
- Compatible with other automotive gear oils

TYPICAL INSPECTIONS

GRADE,SAE	75W-90
GRAVITY, °API	28.2
FLASHPOINT, °F.	420

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Fax: (86)021-64513829

E-mail: info@jichuan.sh.cn

Tel: (86)021-64820099



Shanghai Jichuan Trading

FIREPOINT,°F.	460
POURPOINT,°F.	-45
VISCOSITY:	
SUS@100°F.	520
SUS@210°F.	33
cSt@40°C.	106
cSt@100°C.	15
VISCOSITYINDEX	145
COLOR,D-1500	2.5
BROOKFIELD@-40°C.CPS	100,000

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Fax: (86)021-64513829

E-mail: info@jichuan.sh.cn

Tel: (86)021-64820099