

## JICHUAN ATF+3™

### PRODUCT DESCRIPTION:

JICHUAN ATF+3™ is formulated specifically to meet the Chrysler ATF+3™ specification for automatic transmission fluid. ATF+3™ is manufactured from high quality paraffinic base oils and additives systems to provide excellent oxidative and thermal stability, excellent foam resistance, corrosion and wear protection. ATF+3™ also contains specially selected friction modifiers to meet the demanding frictional requirements of these transmissions.

### TYPICAL USES:

- Designed for use in all Chrysler automatic transmissions and automatic transaxles requiring ATF+®, ATF+2™, or ATF+3™.
- ATF+3™ is not recommended in transmissions using Dexron®, Dexron®-II, Dexron®-IIE, Dexron®-III, and Mercon fluids.

### FEATURES:

- Meets Chrysler warranty requirements.
- Excellent wear protection and quiet, smooth operation.
- Excellent oxidative and thermal stability.
- Protects against rust and corrosion.
- Dyed red.
- Compatible with Chrysler ATF plus automatic transmissions fluid.

### TYPICAL INSPECTIONS

GRAVITY,°API	31.1
FLASHPOINT,°F.	374
POURPOINT,°C.	48
VISCOSITY:	
cP@-40°C.BROOKFIELD	18,400
cSt@40°C.	32.0
cSt@100°C.	7.6
VISCOSITYINDEX	219
COLOR	RED
CALCIUM,WT. %	0.23
ZINC,WT. %	0.059

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY