

JICHUAN TRAC UTF

PREMIUM TRANSMISSION-HYDRAULIC-WET BRAKE FLUID FOR TRACTORS

PRODUCT DESCRIPTION:

JICHUANTRAC UTF is manufactured from premium, high VI, paraffinic base stocks that are fortified with inhibitors to help prevent rusting, foaming, oxidation, chatter, and wear. Other additives are used to protect rubber seals from excessive swelling or shrinking. Special friction modifiers are added to ensure the proper operation of wet brakes and clutches. JICHUANTRAC UTF was developed for use in tractors and other farm implements having combination transmission, differential, wet brake and hydraulic compartment.

TYPICAL USES:

Recommended for:

- Allis-Chalmers PF821, Part No.926371, 926372 and 924282.
- J.I. Case TCHOil, TFD Fluid, JIC 143,144,145, 185, MS 1204, 1205, 1206, 1207, 1210.
- Caterpillar TO-2
- John Deere JDT 303, Hy-Gard, J14B, J14C, J20A/B/C and J21 A
- Ford M2C134-A/B/C, M2C86 B/C, M2C48-B, M2C41 -B M2C53A, M2C136A, M2C77A.
- International Harvester B-6 (Hy-Tran)
- Kubota UDT Hydraulic Transmission Fluid.
- Massey-Fergusson M-1110, M-1127A and B, M-1129A (PemmaTran III) and M-1135
- Minneapolis-Moline 35154, 35202 and 35301.
- Oliver Type 55 and S3727B Fluid.
- Steiger.
- Sundstrand Hydrostatic Transmission Fluid.
- White Q-1826, 17663, 1766, 1722, I 705.

FEATURES:

- Reduced inventory one product for many uses.
- Reduces wear in gears and bearings.
- Stops excessive chatter and grabbing.
- Prevents sludge formation in control valves.
- Anti-wear protects pumps and gear.



Shanghai Jichuan Trading

• Low pour means good response at low temperatures,

· Friction modifier protects wet brakes and clutches.

TYPICAL INSPECTIONS

ITFICAL INSPECTIONS	
GRAVITY,°API	28.0
FLASHPOINT,°F.	420
FIREPOINT,°F.	445
POURPOINT,°F.	-30
VISCOSITY:	
SUS@100°F.	335
SUS@210°F.	60
BROOKFIELDVISCOSITY:	\searrow
cP@-30°F.Max.	70,000
cP@-0°F.Max.	4,500
VISCOSITYINDEX	136
COLOR,D-1500	5.0
VALUES SHOWN HERE ARE TYPICA	AL AND MAY VARY
	<u>у</u>
Shandhai	

Shanghai Jichuan Trading Co.,Ltd. Add: No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai 24h Hotline: 15900706965 Fax: (86)021-64513829 E-mail: info@jichuan.sh.cn Website: www.pingyiao.com

Tel: (86)021-64820099