

JICHUANMATIC DMX-3

THE ULTIMATE AUTOMATIC TRANSMISSION FLUID

PRODUCT DESCRIPTION:

JICHUANMATIC DMX-3 is manufactured to stringent new vehicle manufacturers specifications from premium quality paraffinic base oils blended with a specifically balanced additive combination to provide high oxidation stability, excellent foam resistance, corrosion and wear protection, and heat resistance. This complex fluid is also compounded with a friction-modifying additive to provide smooth lock-up of clutches without chatter.

JICHUANMATIC DMX-3 is a multi purpose fluid that meets and exceeds all current original equipment manufacturers specifications for automatic transmission fluids, including latest, rigorous DEXRON-III-H® and MERCON® revised specifications.

PRODUCT USES:

- General Motors DEXRON®III-H approved, #36159.
- Ford MERCON® approved, #M-040603.
- May be used in late model AMC and Chrysler cars, vans and light trucks as well as most imported cars.
- Allison C-4, Approved #C-430522004
- Recommended where lubricants meeting Caterpillar TO-2 AV is specified.
- Also recommended for Mercedes Benz Passenger Car Manual Transmissions.
- Recommended for GMC Truck & Coach Division vehicles using V, V-H & Super V transmissions.
- Also for Allison AT MT & HT transmissions & Sundstrand & Eaton heavy duty transmissions.
- Low temperature hydraulic and rotary air compressor fluid.

FEATURES:

- Meets car makers warranty requirements.
- Excellent wear protection and quiet, smooth operation.
- Superior thermal and oxidation stability compared to conventional Dexron®II-E Fluids.
- Protects against rust and corrosion
- Outstanding seal compatibility.
- Will not degrade nylon components.
- Dyed red to detect leaks.



Shanghai Jichuan Trading

- Multi-functional fluid Reduced inventory.
- **“Meets H-Specifications”**
(The only ATF you need!)

JICHUAN MULTIPURPOSE ATF APPLICATIONS & MANUFACTURERS APPROVALS

Automatic Transmissions:

• GM Dexron-IIIE • Caterpillar • Ford Mercon • Jaguar • Mercedes-Benz
Passenger Car • Volvo • Mercedes-Benz

Commercial

• SAAB • ZF TE ML-11 & TE ML-14 • Scania • Volkswagen • MAN • Renault •
Leyland Pneumocyclics • Voith • Porsche
• Renke • BMW • Clark • Peugeot S A • Allison C-4 • Twin Disc
Power Steering 6 Vehicular Hydraulics
• Mercedes-Benz • ZF TE ML os • Vickers • Sundstrand ~ Denison

TYPICAL INSPECTIONS

GRAVITY, °API	32.6
FLASH POINT, °F.	385
FIRE POINT, °F.	450
POUR POINT, °F.	-48
VISCOSITY:	
cP@-40°C.Brookfield	18,000
cP@-18°C.Brookfield	1100
cSt@40°C.	35
cSt@100°C.	73
VISCOSITY INDEX	186
COLOR,D-1500	Red

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

® MERCON is a registered trademark of Ford Motors Company

® DEKRON is a registered trademark of General Motors Company

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yin Hai Building, Caoxi Road, Xuhui District, Shanghai

24h Hotline: 15900706965

Website: www.pingyiao.com

Fax: (86)021-64513829

E-mail: info@jichuan.sh.cn

Tel: (86)021-64820099