

# **JICHUANMATIC SYN 1000**

# MERCON V®/ DEXRON III®ATF

#### **PRODUCT DESCRIPTION:**

JICHUANMATIC SYN 1000 MERCON V® / DEXRON III® is a next generation extended life automatic transmission fluid designed for the latest Ford transmission units that require a fluid qualified against the Ford MERCON® specification. Furthermore, it has been formulated to meet the performance requirements for Allison Transmission Division (C-4). MERCON V® is recommended for use in Ford automatic transmissions (except those requiring Ford Type "F" Fluid) and other U.S. and foreign cars and trucks requiring a MERCON V® or MERCON® approved ATF. This product is formulated to exhibit extended life compared with conventional multipurpose ATF's. An excellent choice for transmissions used in severe service, including passenger car and bus fleets as well as towing applications.

#### **TYPICAL USES:**

- Ford MERCON® approval, #M040502.
- Ford MERCON V® approval, #M5040501.
- General Motors approval, Dexron III-H®, #H-36158
- Allison C-4, C-430522004
- Voith approval

## FEATURES:

- Offers superior cold temperature performance.
- Boosted oxidation resistance.
- Extended seal compatibility and improved wear protection.
- Exhibits superior frictional durability and anti-shrudder performance.
- Fortified against rust, corrosion and foaming.
- "Approved for H specifications".
- Dyed red for easy identification.

## TYPICAL INSPECTIONS

GRAVITY,°API	34.75
FLASH POINT,°F.	400
FIRE POINT,°F.	436
POUR POINT,°F.	-65
VISCOSITY:	
cP@-40°C.BROOKFIELD	11,000

Shanghai Jichuan Trading Co.,Ltd.

Add:No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai24h Hotline:15900706965Fax: (86)021-64513829Website:www.pingyiao.comE-mail:info@jichuan.sh.cn

Tel: (86)021-64820099



# Shanghai Jichuan Trading

cP@-20°C.BROOKFIELD 110 cSt@40°C. 33.0 cSt@100°C. 7.03 VISCOSITY INDEX 178 COLOR REI 4-Ball Wear Test (Mercon V ® Proc.) 40Kg, 0.49 2hours, 600rpm, 150°C.	5 3 D 9
cSt@100°C. 7.03   VISCOSITY INDEX 178   COLOR REI   4-Ball Wear Test (Mercon V ® Proc.) 40Kg, 2hours, 600rpm, 150°C. 0.49	3 D Ə
VISCOSITY INDEX178COLORREI4-Ball Wear Test (Mercon V ® Proc.) 40Kg, 2hours, 600rpm, 150°C.0.49	)
COLORREI4-Ball Wear Test (Mercon V ® Proc.) 40Kg, 2hours, 600rpm, 150°C.0.49	)
4-Ball Wear Test (Mercon V ® Proc.) 40Kg, 0.49 2hours, 600rpm, 150°C.	)
2hours, 600rpm, 150°C.	
	(0° 2 2 2 .
Milan	0°.750°
ST STOT	126
Shandhai	

Shanghai Jichuan Trading Co.,Ltd.Add:No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai24h Hotline:15900706965Fax:(86)021-64513829Website:www.pingyiao.comE-mail:info@jichuan.sh.cn

Tel: (86)021-64820099