

Shanghai Jichuan Trading

JICHUAN PIRANHA CHLORINE-FREE TRI-PURPOSE OIL T-35 CF

AN ENVIRONMENTALLY FRIENDLY TRIPLE PURPOSE LUBRICANT - MACHINE OIL - HYDRAULIC OIL - CUTTING

PRODUCT DESCRIPTION:

JICHUAN PIRANHA TRI-PURPOSE OIL T-35 is a superior tri-purpose, transparent*, non-corrosive, light colored, anti-mist cutting oil fortified with a special chlorine-free extreme pressure additive and lubricity additive. The tri-purpose features of this oil allows its use as a cutting oil, hydraulic oil and machine oil in automatic screw

machines. This eliminates the intermingling of cutting oil with the machine oils and hydraulic oils as the result of leakage from one system to another. The contamination of machine oil and hydraulic oil by active corrosive cutting oils can have serious consequences in automatic screw machines. This can best be avoided by using one oil for all three applications.

TYPICAL USES:

- Used as cutting oil, machine oil and hydraulic oil in automatic screw machines.
- Well suited for machining non-ferrous metals such as brass, bronze, copper, aluminum and magnesium.
- Used in machining steel and its alloys where machining requirements range from light to moderately severe (60-100 machinability).
- Lubricity additive makes product an ideal way lubricant.
- Anti-mist allows use of product in high speed cutting operations.

FEATURES:

- Triple purpose reduced inventory.
- Economical.
- Anti-mist/transparent good visability of workpiece.
- Eliminates contamination problem between machine oil and cutting oil.

Tel: (86)021-64820099

- Non-corrosive to work or machine parts (non-staining).
- · Good workpiece surface finish.
- High lubricity for long tool life.
- Chlorine-free nature of this oil makes it readily disposable.
- · Dyed green for easy identification.

Shanghai Jichuan Trading Co.,Ltd.

Add: No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai 24h Hotline: 15900706965 Fax: (86)021-64513829 Website: www.pingyiao.com E-mail: info@jichuan.sh.cn



Shanghai Jichuan Trading

Tel: (86)021-64820099

TYPICAL INSPECTIONS

GRAVITY,°API	29.9
FLASH POINT,°F.	415
FIRE POINT,°F.	445
POUR POINT,°F.	-10
VISCOSITY:	
SUS@100°F.	163
SUS@210°F.	45
cSt@40°C.	31.8
cSt@100°C.	5.75
VISCOSITY INDEX	123
COLOR	GREEN

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

value art

Add: No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai 24h Hotline: 15900706965 Fax: (86)021-64513829 E-mail: info@jichuan.sh.cn Website: www.pingyiao.com

^{*} Note: This product is darker due to new state of the art technology.