

Shanghai Jichuan Trading

JICHUAN PM OIL

PREMIUM QUALITY PAPER MACHINE OIL

PRODUCT DESCRIPTION:

JICHUAN PM OIL is formulated from premium quality, high VI, paraffinic base oils combined with selected additives package to provide resistance to foaming, rusting, corrosion and oxidation. In addition, it contains an effective anti-wear agent and detergent-dispersant to keep contaminants suspended in the oil. Demulstbility agent provides rapid water separation with conventional setting or centrifuging equipment.

TYPICAL USES:

• JICHUAN PM OIL 150 and 220 is recommended for use in the circulating systems of paper machine dryer section of those manufactured by; Beloit, Black-Clawson, Rice-Barton, and others.

• Recommended for use in all types of industrial reduction gears and gear head motors where high Timken values are not required.

• Also used and recommended for vacuum pump sand hydraulic systems.

FEATURES:

High oxidation stability assures long service life.

• Effective detergent-dispersant keeps contaminants in suspension and prevents formation of sludge.

• Excellent thermal stability permits use under high temperature conditions found in dryer roll bearings.

- High alkaline reserve provides protection against corrosive acids and rusting.
- Mild EP additives permit use in industrial gear sets.
- Miscible with other paper mill circulating oils.

I PICAL INSPECTIONS		
GRADE.ISO	150	220
GRAVITY,°API	27.6	26.5
FLASHPOINT,°F.	465	475
FIREPOINT,°F.	515	525
POURPOINT,°F.	15	15
VISCOSITY:		
SUS@100°F.	790	1165
SUS@200°F.	78	95
cSt@40°C.	150	220

TYPICAL INSPECTIONS

Shanghai Jichuan Trading Co.,Ltd.

Add:No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai24h Hotline:15900706965Fax:(86)021-64513829Website:www.pingyiao.comE-mail:info@jichuan.sh.cn

Tel: (86)021-64820099



Shanghai Jichuan Trading

	600-520		100 C
cSt@100°C.	14.4	18.6	
VISCOSITYINDEX	95	94	
COLOR,D-1500	4.0	5.0	
ZINC,WT.%	.065	.085	

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY Shanahai Jichuan madina co. Itd.

Shanghai Jichuan Trading Co.,Ltd.Add:No 1201, Yinhai Building, Caoxi Road, Xuhui District, Shanghai24h Hotline:15900706965Fax:(86)021-64513829Website:www.pingyiao.comE-mail:info@jichuan.sh.cn

Tel: (86)021-64820099